

NAME

krb5_keytab.conf - configuration file for krb5_keytab(8)

SYNOPSIS

krb5_keytab.conf

DESCRIPTION

krb5_keytab.conf is the configuration file for krb5_keytab(8). The syntax is a Perl snippet which is evaluated and is expected to set the following variables:

@admin_users	is a list of users who are allowed to perform administrative functions. That is, they can operate on other user's keytabs and avoid the system encryption type policies.
@allowed_enctypes	is a list of acceptable encryption types that even administrative users cannot over-ride.
\$default_krb5_lib	is the default Kerberos library version if it is not specified.
%krb5_libs	is a hash mapping Kerberos library versions to an array ref of supported encryption types.
%krb5_lib_quirks	is a hash mapping Kerberos library versions to an array ref of keytab management bugs (quirks) that must be considered when constructing or testing a keytab.
\$use_fetch	is a boolean value which tells krb5_keytab(8) whether it should attempt to fetch keys from the KDC. By default the KDC will refuse these requests, so only enable this option if you have configured the KDC allow the fetching of keys. See <i>\$allow_fetch</i> in krb5_admind.conf(5). This value defaults to 0.
%user2service	is a hash mapping users to an array ref containing additional service principals that the user may request to be placed in its keytab. This mechanism will eventually be replaced with a more general mechanism which allows for hostbased specification of this concept.
%user_libs	is a hash mapping users to an array ref containing a list of acceptable Kerberos libraries which the user may use. Administrative users may not over-ride this restriction.

Syntax errors will terminate parsing causing all subsequent configuration to be ignored and so it is critical that they not be present.

SEE ALSO

krb5_keytab(8).

AUTHORS

krb5_keytab.conf was written by Roland C. Dowdeswell.